

# FTTH box for 48 fibers 015VQ



## Description

### Application:

Optical Telecommunication Networks  
LAN, Optical fiber Communication Network  
CATV Networks  
FTTH access Network  
PON, G-PON

Delivery unassembled (shrink splice holder, max. 48 splices double layed, 24 x shrink protection and material for wall mounting included)

## General data

Scope of application	Outdoor
Mounting	Wall mounting
Possibility of mast mounting	True
Material	Plastic
Colour	Grey
Cable entry without cable gland	24 x 2-3mm
Cable entry with cable gland	2 x PG19
Number of Fibres	48
Type of Splice protection	Thermo
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Max. Assembly (Adapter)	24
With Fiber overlength cassette	True
Hinged splice cassette	True

### General data

Holder for splitter	True
Holder for gas blocker	True
Cable sheath support	True

### Mechanical characteristics

IP Protection	IP65
Foreign body and contact protection	Protection against ingrees of dust
Water protection	Protection against jet water

### Dimensions

Dimensions	232 x 359 x 130.5 mm
------------	----------------------

### Environmental conditions

Temperature Range	-25 – 70 °C
-------------------	-------------

### Available variants

Article no.	Title	Access Control
015VQ	FTTH IP65 Connectionbox for 48 fiber, 24 adapter and Fiber overlength box	Special screw/ Seal

### Technical drawings

