

FTTH box for 96 fibers 015YM



Description

015YM closure is designed to seal without screws. The compact size and flip-over cover bring easy operation as well as complete function. The splice trays are jointed with a hinge at one side, which makes the operation in each tray easier. It is designed to prevent from operation damage. The fiber access terminal closure is able to hold up to 16 subscribers and 96 splicing points as closure. It is used as a splicing closure and a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

Water-proof design with IP-68 Protection level.
Integrated with 4 flap-up splice cassette and adaptor holder.
Impact test 1K10. Pull Force 100N. Full Rugged design.
All stainless metal plate and anti-rusting bolts nuts.
2 pcs of 1x8 splitter can be installed as an option.
Mechanical sealing structure and mid-span cable entry.
4 ports for the feeder cables (2x up to 18 and 2x up to 21 mm), 16 ports cable entrance for drop cable (3 mm).
24 adaptors (SC Simplex or LC Duplex) for drop cable patching.

Basic data

Dim. 388 x 242 x 128 mm, Weight 4.5 kg, Working temperature -30 to +80 °C, Material Black Polipropylene

Standard Accessories

Splice cassettes and cable management tool, installation bolts and nuts, protection sleeves, hose clamp, cable tube, wrench, cover holder, rubber seal for cable entrance.