

10/100M WDM Fiber Media Converter with External Power Supply



Standards: IEEE802.3 IEEE802.3u IEEE802.3x 10/100Base-TX 100Base-FX

FE-XXX Models	Fiber mode	Max distance	Wave length	ST/SC
HM-100M-B13(15)	Bidi -MM	2 km	1310nm/1550nm	SC
HM-100S-B13(15)	Bidi -SM	20 km	1310nm/1550nm	SC
HM-100S.40-B13(15)	Bidi -SM	40km	1310nm/1550nm	SC
HM-100S.60-B13(15)	Bidi -SM	60km	1310nm/1550nm	SC
HM-100S.80-B13(15)	Bidi -SM	80km	1310nm/1550nm	SC

TP Port Rate: 10/100Mbps N-Way Auto-negotiation

Fiber Port Rate: 100Mbps

Duplex Mode: Full-Duplex / Half-Duple N-Way Auto-negotiation

UTP Ports: RJ-45 UTP

Fiber Ports: Simplex SC Port

LED Indicators: TX LINK, FX LINK, TX ACT, FX ACT, PWR, FDX.

Power Requirement: 1A@ +5VDC

Ambient Temperature: 0~60

Humidity: 5%~90%

Dimensions: 95mm(W)×70mm(D)×26mm(H)

FCC Part 15 Class A & CE Mark.