

10/100/1000M WDM Fiber Media Converter with External Power Supply



Standards: IEEE802.3、IEEE802.3u 、IEEE802.3z/ab. 10/100/1000Base-T/SX/LX

FX-GBXXX Models	Fiber mode	Max distance	Wave length	ST/SC/FC
HM-GB13/1502-SC	Bidi -MM	2 km	1310nm/1550nm	SC
HM-GB13/1520-SC	Bidi -SM	20 km	1310nm/1550nm	SC
HM-GB13/1540-SC	Bidi -SM	40 km	1310nm/1550nm	SC
HM-GB13/1560-SC	Bidi -SM	60 km	1310nm/1550nm	SC
HM-GB13/1580-SC	Bidi -SM	80 km	1310nm/1550nm	SC
HM-GB13/15100-SC	Bidi -SM	100 km	1310nm/1550nm	SC
HM-GB13/15120-SC	Bidi -SM	100 km	1310nm/1550nm	SC

TP Port Rate: 10/100/1000Mbps

Fiber Port Rate: 1000Mbps

Duplex Mode: Full-Duplex / Half-Duplex N-Way Auto-negotiation

UTP Ports: RJ-45 UTP

Fiber Ports: ST /SC/FC Multi-mode or Single-mode Simplex Fiber Port

LED Indicators: PWR, FX LINK, TP100, TP1000, TP TX, TP RX.

Power Requirement: 2A@ +5VDC.

Ambient Temperature: -20~75°C

Humidity: 5%~90%

Dimensions: 95mm(W)x70mm(D)x26mm(H)

FCC Part 15 Class A & CE Mark.