

# Tesni vtič / Bare Fiber Adapter



## Opis / Description

Testni vtič je poseben hitro montažni vtič namenjen spajanju golega vlakna z merilno opremo. Testni vtič z vlaknom spojimo in razdvojimo v nekaj sekundah. Največ se uporablja za testiranje kablov na kolutu pred inštalacijo, za nujna popravila optičnih segmentov ter za laboratorijske in druge namene.

---

*The Bare Fiber Adapter is a most affordable and easy method for temporarily connecting bare fiber with all industry standard connectors. The system provides a simple and easy method to quickly interconnect any standard fiber connector to a piece of unterminated (bare) fiber to meet service, test or communication requirements.*

## Podatki / Specification

<i>Insertion Loss</i>	$\leq 0.2\text{dB}$
<i>Retentiveness</i>	200-600g
<i>Mating Durability (1000 times)</i>	$\leq 0.2\text{dB}$
<i>Exchangeability</i>	$\leq 0.2\text{dB}$
<i>Sleeve material</i>	Zirconia Ceramic
<i>Withdrawal Force</i>	2-6 N
<i>Temperature</i>	- 40 to 85
<i>Standard</i>	Bellcore GR-326

## Podatki za naročilo / Ordering information

Koda / Item	Ime izdelka / Description
09333	SC testni vtič za golo vlakno / SC Bare fiber adapter
09335	LC testni vtič za golo vlakno / LC Bare fiber adapter
98337	FC testni vtič za golo vlakno / FC Bare fiber adapter