



K33


IPAAS Core Alignment Splicer



Benefits and Features

- Wide 5.0 inch color LCD monitor with Electrostatic touch screen & bidirectional operation system.
- User friendly GUI
- Powerful lithium polymer battery with large capacity.
- Lowest Splice Loss.
- Resistance to Shock, Dust and Water
- LED lamp installed on the wind cover for low light condition


PATENTED



Electrode Life

Up to **18,000** splices

PATENTED



Rotating Blade Life

Up to **75,000** fibers

Specifications

CATEGORY	DESCRIPTION
Fiber alignment	IPAAS Core Alignment
Applicable fibers	SM(G.652), MM(G.651), DS(G.653), NZDS(G.655), SM(G.657 A1,A2/B2,B3), SM(G.654 E)
Fiber count	Single fiber
Applicable fiber dimensions	Cladding diameter: 80~150µm, Coating diameter: 100µm~3mm
Fiber cleave length	250µm: 5~16mm, 900µm: 8~16mm
Splicing modes	Splice mode: 300, Heat mode: 100
Average splice Loss	SM: 0.02dB, MM: 0.01dB, DS: 0.04dB, NZDS: 0.04dB
Return loss	> 60dB (Typical)
Splicing time	Typical 6 sec. (Quick Mode)
Splice loss estimate	Available
Sleeve heating time	9 sec (IS-45 Sleeve, IS-45 mode), 13 sec (IS-60 Sleeve, IS-60 mode)
Applicable protection sleeve	32mm, 40mm, 60mm (Fiber) / 28mm or 32mm (Connector)
Storage of splice result	The last 10,000 results to be stored in the internal memory. (Image 10,000 results) External SDHC Memory & WiFi slot
Tension test	1.96N ~ 2.25N
Operating conditions	Altitude: 0~5,000m above sea level, Temperature: -10°C~50°C, Humidity: 0~95%, Wind: 15m/s, Non-condensing, Dust proof, Water proof, Shock proof
Storage conditions	Temperature: -40°C~80°C, Humidity: 0~95%
Dimensions	130(W) x 158(L) x 138(H)mm (EXcluding bumper)
Weight	2.25kg (Including battery)
Viewing method and display	Two CMOS cameras and 5.0-inch color LCD monitor with Electrostatic touch screen
Fiber view and magnification	X/Y 200X, Max 400X
Power supply	100~240V AC
Battery life with heat-shrink	Typical 200 cycles (4700mAh)
Electrode life	Up to 18,000 splices
Terminals	USB

Standard Package

CATEGORY	MODEL	Q'ty
Arc Fusion Splicer	SWIFT K33	1
User guide CD	-	1
Spare electrode	EI-23	1 pair
Transporting Case	Hard Case	1
Battery	K3347(4700mAh)	1
AC Adapter	100-240V	1
Cleaver	CS-01BT	1
Manudal stripper	CF-02	1
Alcohol dispenser	PP	1
Tool box	-	1
USB Cable	-	1

Optional Package

CATEGORY	MODEL
Battery	K3347(4700mAh)
Cleaver Blade	BI-07
Electrode	EI-23
External Power	DC 12V available for car cigar jack
Sleeve	S-160 (60mm), S-140 (40mm)
Sleeve Clamp	-
Sleeve Loader (2ea)	-
Optical Fiber Holder	HS-250, HS-900, HS-2.5F, HS-IN, HS-SC/FC, HS-ILC, HS-ST, LS-900(Loose tube)
SOC Connector	SC, LC, FC, ST (refer to FTx solution catalogue)
Work Belt	-

* Design, standard/optional package and specification shown above are subject to change with or without notice.

UCLSWIFT KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509) | Tel +82 42.671.5610 | Fax +82 42.671.5612 | sales@uclswift.com

USA America ILSintech LLC., 4230 LBJ Freeway, Suite.149 Dallas, TX 75244, USA | (+1) 972 556 0916, info@americailsintech.com

INDIA ILSintech Trading India Pvt.Ltd, 302-303, Ashirwad Comercial Complex,D-1, Green Park, New Delhi 110016, India | (+91) 11 4055 5954, insintech@ilsintechindia.com

CHINA ILSin Optical Communication Equipment Trade(Shanghai) Co.,Ltd.
Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950, sh0923@uclswift.com

EUROPE UCL SWIFT Co.,Ltd, odštěpný závod, Zirovnicka 2/2389 10600 Praha 10, Czech Republic | (+420) 725 001 757, dean@uclswift.com

RUSSIA UCL RUS LLC., Moscow, 22nd km of Kiev highway, 4, Rumyantsevo Business Park, p. 4, block D, office 305 zip code : 108811,
(+7) 495-169-00-29, (+7) 926-875-38-68, sales@uclrus.ru

INDONESIA FACTORY Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia

