

MK01DA

Outer Jacket Cable Stripper

- Designed for precision stripping of a variety of insulation types including rubber, PVC, nylon and cotton
- Also recommended for cutting copper screening of coaxial cables from 8 to 38 mm (0.31 to 1.5 in.)
- Adjustable blade depth up to 4.5 mm (0.18 in.)
- Blade depth setting can be locked to assure consistent repetitive operations
- Adjustable hook head allows for variation in blade force for harder materials
- Stripping action is circumferential, longitudinal and spiral for removal of jacket and insulation



Application	Wire Size, mm O.D.	Wire Size, Inches O.D.
Cable Stripping	8 mm to 33 mm	0.31 in. to 1.5 in.

- Replacement Blade: Part No.: 39381
- Weight: 159 g (5.6 oz)
- Length: 163 mm (6.4 in.) closed
- Part No.: 39922

MK04

Cable Jacket Stripper

- Cable stripper for outer jackets & insulation on large diameter cables
- Heavy duty construction for industrial environments
- Rotary cut to a longitudinal cut along the cable length for end stripping
- Spiral cut for end stripping
- Spiral cut for mid-span stripping
- Spiral cutting feature provides easier removal of soft jackets and on larger cables
- Adjustable blade up to 0.20 inches (5 mm) cutting depth
- Blade depth setting can be locked to assure consistent repetitive operations
- Roller support of cable for smooth stripping action
- Wheel blade applications available – contact Customer Service for sizes and applications U.S.: 860-635-2200 U.K.: 44-1384-400070



Model	Cable Size Range In. O.D.	Cable Size Range mm O.D.	Part No.
MK04	0.79 in. to 2.36 in.	20 to 52	39376

- Replacement Fixed Blade Assembly: Part No.: 39379
- Replacement Fixed Blade Cartridges (FC2) Part No.: 39377 for larger O.D. cable & (FC3) Part No.: 39378 for smaller O.D. cable
- Weight: 1.5 lbs (680 g)
- Size: 3.7 x 1.7 (head) x 9.8 in. (95 x 42 x 250 mm)